Low Cost Retrofit List

10 Low Cost Ways to Harden Your Home

- 1. When it is time to replace your roof, replace it with fire-resistant Class A roof material.
- 2. Block any spaces between your roof covering and sheathing (bird stops).
- 3. Install non-combustible corrosion resistant metal gutter covers on gutters to prevent the accumulation of leaves and debris in the gutter.
- Cover your chimney and stovepipe outlets with noncombustible corrosion corrosion-resistant metal mesh screen (<u>spark arrestor</u>), with 3/8-inch to 1/2-inch openings.**
- 5. Cover all vent openings with 1/16-inch to 1/8-inch noncombustible corrosion resistant metal mesh screens.**
- 6. Caulk and plug gaps greater than 1/16-inch around exposed rafters and blocking to prevent ember intrusion.
- 7. Inspect exterior siding for dry rot, gaps, cracks and warping. Caulk or plug gaps greater than 1/16-inch in siding and replace any damaged boards, including those with dry rot.
- 8. Install weather stripping to gaps greater than 1/16-inch in garage doors to prevent ember intrusion. The stripping must be compliant with UL Standard 10C.
- 9. When it's time to replace your windows, replace them with multi-paned windows with at least one pane of tempered glass.
- When it's time to replace your siding or deck, use compliant noncombustible, ignition-resistant, or other <u>materials approved by the Office of the State Fire</u> Marshal (OSFM).

5 No Cost Ways to Create Defensible Space and Enhance the Effects of a Hardened Home

- 1. Regularly clean your roof, gutters, decks, and the base of walls regularly to avoid the accumulation of fallen leaves, needles and other flammable materials (see <u>Defensible Space</u> for more details).
- 2. Ensure all combustible materials are removed from underneath, on top of, or within five feet of a deck.
- 3. Remove vegetation or other combustible materials that are within five feet of windows and glass doors.
- 4. Replace wood mulch products within five feet of all structures with noncombustible products such as dirt, stone, or gravel.
- 5. Remove all dead or dying grass, plants, shrubs, trees, branches, leaves, weeds, and pine needles within 30 feet of all structures or to the property line.

^{*}This list was developed as a best practices guide and to assist homeowners to ensure their home is more ignition-resistant from wildfires. Low cost can be subjective. Some of these items are based on upgrading to more stringent materials when that feature is up for replacement due to normal maintenance or lifespan, i.e. roofs.

^{**} Do not use fiberglass or plastic mesh as they can melt or burn.